

## Online Resource 2: Captions for Animations accompanying “The 2022 Chaos Canyon landslide in Colorado: insights revealed by seismic analysis, field investigations, and remote sensing”

Kate E. Allstadt<sup>1\*</sup>, Jeffrey A. Coe<sup>1</sup>, Elaine A. Collins<sup>1</sup>, Francis K. Rengers<sup>1</sup>, Anne Mangeney<sup>2</sup>, Scott Esser<sup>3</sup>, Jana Pursley<sup>4</sup>, William L. Yeck<sup>1</sup>, John J. Bellini<sup>4</sup>, Lance R. Brady<sup>5</sup>

\*corresponding author: [kallstadt@usgs.gov](mailto:kallstadt@usgs.gov)

1) U.S. Geological Survey Geologic Hazards Science Center, Golden, CO, USA

2) Université Paris Cité, Institut de Physique du Globe de Paris, CNRS, F-75005 Paris, France and Institut Universitaire de France

3) Rocky Mountain National Park, National Park Service, Estes Park, CO, USA

4) National Earthquake Information Center, U.S. Geological Survey, Golden, CO, USA

5) National Uncrewed Systems Office, U.S. Geological Survey, Denver, CO, USA

Online Resource 2 (OR2\_AnimationCaptions.pdf): Captions for SHALTOP simulations

Online Resource 3 (OR3\_Main28June2022\_Coulomb\_delta29p5.mp4): Best fitting SHALTOP simulation using the Coulomb rheological law for the main 28 June 2022 landslide. This simulation uses a single friction angle of  $\delta=29.5^\circ$  and corresponds to Figure S5. Animation shows the evolution of flow thickness over time.

Online Resource 4 (OR4\_Remobilization\_Hayashi1992\_mean\_Coulomb\_delta23.mp4): SHALTOP simulation of a remobilization of the entirety of the Chaos Canyon landslide deposits using the Coulomb rheological law with an effective friction coefficient ( $\mu$ ) estimated using the mean H/L value for a volume of 2.1 million m<sup>3</sup> from the relationship derived by Hayashi and Self (1992) for subaerial non-volcanic landslides,  $\mu=0.42$  ( $\delta=22.8^\circ$ ). This simulation corresponds to Figure S6b in Online Resource 1.

Online Resource 5 (OR5\_Remobilization\_Hayashi1992\_plus2std\_Coulomb\_delta28.mp4): Same as Online Resource 6 but low mobility scenario estimated using an effective friction coefficient 2 standard deviations below the mean using data compiled by Hayashi and Self (1992) for subaerial non-volcanic landslides,  $\mu=0.52$  ( $\delta=27.5^\circ$ ). This simulation corresponds to Figure S6a in Online Resource 1.

Online Resource 6 (OR6\_Remobilization\_Hayashi1992\_minus2std\_Coulomb\_delta19.mp4): Same as Online Resource 7 but the high mobility scenario in which the effective friction coefficient was estimated using 2 standard deviations below the mean  $\mu=0.35$  ( $\delta=19.2^\circ$ ). This simulation corresponds to Figure S6c in Online Resource 1.

Online Resource 7 (OR7\_Remobilization\_matchHayashiHL\_mul\_delta11.mp4): Alternate SHALTOP simulation of a remobilization of the deposits where the  $\mu(l)$  rheology was tuned until the runout distance achieved an H/L value equal to that predicted for this landslide volume by Hayashi and Self (1992), H/L=0.42. This was achieved for friction angles of  $\delta_1=11^\circ$ ,  $\delta_2=21^\circ$  and a mean particle size of 1 m. This simulation corresponds to Figure S7a in Online Resource 1.

Online Resource 8 (OR8\_Remobilization\_Lucas2014\_mean\_delta18.mp4): Alternate SHALTOP simulation of a remobilization of the deposits where the Coulomb rheology law was utilized with the effective

friction angle estimated by Lucas et al. (2014) of  $\delta=18^\circ$  ( $\mu=0.32$ ). This simulation corresponds to Figure S7b in Online Resource 1.

Online Resource 9 (OR9\_Remobilization\_Corominas\_debrisflow\_mean\_delta12.mp4): Alternate SHALTOP simulation of a remobilization of the deposits where the Coulomb rheology law was utilized with the effective friction angle estimated as the H/L ratio by Corominas (1996) for debris flows  $H/L=\delta=12^\circ$  ( $\mu=0.21$ ). This simulation corresponds to Figure S7c in Online Resource 1.